

## Product Description: Treatex Colour Tones

Wood doesn't always match the other colours in your home so Treatex have developed a range of colour tones to assist in the matching process. As various timbers will take colours differently, we do advise to do a sample before applying to the whole area.

- **Colours**, Spruce, Grey, Slate, Ebony, Antique Oak, Dark Oak, Medium Oak, Mahogany
- **The pigments** are colourfast. Using natural pigments enhances the grain & strengthens the colours.
- **Intermixable**, all Treatex Colour Tones can be mixed to make an infinite range of colours.
- **Easy to apply**, No overlapping, applicator marks.

### Recommended Tools:

80 -120 grit screen, Stirring stick, paint tray, brush, flexible trowel. Lint free cloth, slow buffer Clark RS16

**Clean tools:** with WHITTLE WAXES SPECIAL-THINNER.

**Coverage Rate:** Approximately 20m<sup>2</sup> per litre

**Coats needed:** 1 coat system

**Container sizes:** 500ml, 1L, 2.5L, 5L,

**Risk of spontaneous combustion.**

Dispose carefully of cloths.

**Drying time:** Allow to dry for at least 12 hrs to 24 hours – Warmth and ventilation will speed up the drying process. Cold and humidity may slow down the process.

**Storage:** Indefinite in sealed container.

### Floor Preparation:

1. If the surface to be treated is rough, sand smooth with 80-120 grit sandpaper (no sanding is required between coats).
2. If a previous surface coating finish is present e.g. varnish, lacquer, hard wax oil etc. sand back to bare wood, again using 80-120 grit sandpaper.
3. Remove any dust, dirt and make sure the surface to be treated is clean, free of contaminates and thoroughly dry.
4. We advise that when using colours, sufficient product is purchased to complete the whole project and where more than one tin is required it is advisable to mix tins together before use.
5. Stir tins and ensure product is at room temperature before use.
6. We strongly recommend a small trial application.
7. When colouring a previously oiled surface a trial application is essential.
8. Tinting –up to 5% in 1<sup>st</sup> of clear coats

### Application Technique: By Machine

1. Apply the stain with a paint brush around the edges of the room,
2. Use a lint free cloth to remove excess stain as you go.
3. Don't worry about overlapping areas where the excess has already been clothed off, you will not leave join marks.
  - Pour a small puddle the size of your palm on the floor. Place the buffing machine on the puddle of colour tone. Remove by slow buffer, Clark RS16
  - Or if you prefer apply with a flexible trowel, do not leave any residue on the surface and remove with a slow buffer Clark RS16
4. The drying time after the initial application will take between 12 to 24 hours, depending on atmospheric conditions.
5. During the drying time do not walk on the surface.
6. The floor then must be protected with one of our Treatex Hardwax Oil or Whittle Waxes Hardwax Oil.

**Application on furniture or smaller surfaces:**

1. One coat of *Treatex Colour* Tone should be brushed or rolled on thinly and evenly.
2. Remove any excess product immediately with a lint free cloth.
3. Allow to dry – maintaining warmth and ventilation will enable the surface to dry faster.
4. Once dry, seal with two coats of Treatex Hardwax Oil or Whittle Waxes Hardwax Oil.

**Water Popping or Grain Popping:**

This will intensify depth of colour.

1. Mist the surface with a light spray of water.
2. Allow to thoroughly dry (approx. 3 hours)
3. Apply the colour following the application instructions above.

**Ingredients:** jojoba oil, linseed oil, sunflower oil, beeswax, candelilla wax and carnauba wax. The pigments used are natural pigments, some of which have been used as colorants since prehistoric times.



**Warning**

**H226 Flammable liquid and vapour.**

**P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.**

**P241.3 Use explosion-proof electrical equipment. P243**

**Take precautionary measures against static discharge. P280**

**Wear protective gloves/protective clothing/eye protection/face protection. P303+P361+P353 IF ON SKIN (or hair):**

**Take off immediately all contaminated clothing. Rinse skin with water/shower. P403+P233 Store in a well-ventilated place. Keep container tightly closed.**

**Disclaimer:** Our technical advice in written form is given in good faith and on the basis of experiments, but it is only non-binding advice and does not release you from the obligation to test the products supplied by us as to their suitability for the particular purpose. Application, use and processing of the products outside our direct control are entirely your responsibility. Naturally we guarantee consistent quality of our products corresponding to the original sample. With release of new product information the previous information loses validity.