



Product Description: Whittle Waxes Wax Finish

Maintains all interior surfaces with a beautiful matte finish.

- **Suitable for:** All timber and cork surfaces indoors, as well as linoleum, PVC, synthetic lining, laminate, stone, marble, baked clay and ceramic floor tile.
- **Properties:** Whittle Waxes WAX FINISH is antistatic, anti-slip and dirt-repellent. At the same time, it maintains and protects the surface and keeps it breathable. The product dries clear.
- **Safe Meets Australian and German regulations on combustible liquids. Safe** for humans, animals and plants after drying. Food and toy safe. Contains no biocidal substances or preservatives.

Recommended Tools: Brush, cotton cloth, or white pad on a buffing machine, possible white nylon pad on buffing machine to remove lines.

Clean tools: with WHITTLE WAXES SPECIAL-THINNER.

Sheen Levels: Matte

Coats needed: Single coat system

Coverage Rate: Approximately 30-40 ml per m², i.e. 1 liter Whittle Waxes Wax Finish yields between 25-50 m² per coat, depending on application technique and substrate.

Drying time: at 20°C and approximately 55% humidity is approximately 1-3 hours.

Storage: Cool but frost-free. 2 years shelf-life in unopened containers. Close container airtight after use.

Container sizes: 1 liter, 2.5 liters, 10 liters and larger.

Preparation

1. The surface must be clean, free of dust and oil and dry.
2. It is essential that untreated timber be pre-treated with appropriate Whittle Wax Product
3. Contamination may be removed Whittle Waxes Preparation cleaner, Please refer to our Preparation information sheet first.
4. Acts differently on differing surfaces. Trial coats are absolutely necessary.

Application of Wax Finish on previously treated surfaces:

1. Shake well before and during use.
2. Apply an evenly thin layer of Whittle Waxes WAX FINISH to the pre-treated surface using a brush, cotton cloth or machine.
3. After drying (approximately 1-3 hours) buff immediately.
4. Allow remaining matte areas to dry and buff again.
5. Remove possible lines caused by buffing with white nylon pad.
6. Apply Whittle Waxes WAX FINISH as needed.

Cleaning and Care: Please read the Whittle Waxes Cleaning, Care, and Maintenance information available on website.

Ingredients: Isoaliphates, refined natural oils.



International GHS Safety Notes; H304 May be fatal if swallowed and enters airways. EUH066 Repeated exposure may cause rough and chapped skin. P101 If medical advice is needed, keep packaging or label handy. P102 Keep out of the reach of children. P103 Read label before use. P301 + P310 If swallowed: Immediately call a poison centre or physician. P331 Do not induce vomiting. P405 Store locked up. Give only completely emptied containers for recycling. Dried residue can be disposed of as household waste or as construction waste. Dispose of liquid residues at a collection point for old paint. ASN No.: 080112.

Disclaimer: Our technical advice in written form is given in good faith and on the basis of experiments, but it is only non-binding advice and does not release you from the obligation to test the products supplied by us as to their suitability for the particular purpose. Application, use and processing of the products outside our direct control are entirely your responsibility. Naturally we guarantee consistent quality of our products corresponding to the original sample. With release of new product information the previous information loses validity.

whittle WAXES Factory 13, 25 Quanda Road, Coolumb Beach, 4573, QLD, AU Tel: 1300 326 929 info@whittlewaxes.com.au

www.whittlewaxes.com.au