



Product Description: Whittle Waxes Universal Exterior Cleaner

A simple application for the thorough cleaning of WPC. (Wood Plastic Composites)

- Suitable for: Thorough cleaning of WPC (Wood Plastic Composites), resista, wicker and rattan.
- The specially developed UNIVERSAL EXTERIOR CLEANER will eliminate atmospheric pollution, algae, discolouration, grease, oil and other contaminants.
- The eco-friendly cleaning concentrate removes dirt also from corrugations, cracks and grooves.

Recommended Tools: Stirring stick, Bucket, measuring cup. Scrubber, cleaning pad, or cleaning machine.

Clean tools: Soapy water

Drying time: Drying time after application is approximately 12 - 24hrs, before applying Universal Exterior Protection.

Coverage Rate: Approximately 15 - 80 ml/m², i.e. 1 litre of undiluted UNIVERSAL EXTERIOR CLEANER covers about 12 - 65 m² per coat.

Coats needed: Single treatment system. For heavily soiled surfaces 2 treatments or more.

Container sizes: 1 litre

Application temperature: not below + 8 ° C, not in direct sunlight.

Storage: Cool but frost-free. Can be stored for 3 years in unopened containers. Fill open containers into smaller, suitable containers, which are airtight and use soon.

Preparation:

Different surfaces react differently; Make a test before use in an inconspicuous place.

Application:

1. Apply UNIVERSAL EXTERIOR CLEANER (depending on the degree of contamination) undiluted or at maximum dilution with water of 1:10 to the pre-wetted WPC surface.
2. Allow to soak about 3- 5 minutes.
3. Then brush off with a scrubbing brush or cleaning pad (pad) and water.
4. Do not allow UNIVERSAL EXTERIOR CLEANER to dry on the surface but work in sections.
5. Remove the loosened dirt and rinse well with clear water.
6. Repeat the process if necessary.
7. After applying UNIVERSAL EXTERIOR CLEANER and drying well for about 12 -24 hrs and apply a protective oil, for example, UNIVERSAL EXTERIOR PROTECTION to prevent weathering and new contamination.

Ingredients: Water, <5% anionic surfactants, <5% non-ionic surfactants, <5% phosphates, butyl glycol.

Although our products are naturel and ecological please;

- Keep out of reach of children. May cause allergic reactions.
- Completely empty containers before recycling.
- Dried waste material can be disposed of as household waste or construction waste.
- Liquid disposed of at paint collection facility.
- In case of contact with the skin, rinse immediately with clear water.
- It must not be allowed to escape into the sewage system or in flowing water.
- Do not leave waste sanding powder in vacuum unit

Disclaimer: Our technical advice in written form is given in good faith and on the basis of experiments, but it is only non-binding advice and does not release you from the obligation to test the products supplied by us as to their suitability for the particular purpose. Application, use and processing of the products outside our direct control are entirely your responsibility. Naturally we guarantee consistent quality of our products corresponding to the original sample. With release of new product information the previous information loses validity.

