

WHITTLE WAXES PREPARATION CLEANER INFORMATION SHEET



whittle
WAXES

Product Description: Whittle Waxes Preparation Cleaner

Multi surface and Laminate Cleaner which aggressively removes grease, oil, and wax in preparation for recoating.

- For a thorough cleaning of all floors such as hardwax oiled timber, parquet, plastic, cork, PVC, linoleum, laminate, natural and artificial stone floors, tiles and rubber floors.
- Whittle Waxes PREPARATION CLEANER, cleans waxed and oiled floors before refurbishing and thereby removes old gloss and polymer layers, waxes, oil films and other impurities.

Recommended Tools: Stirring stick, bucket, measuring cup. Scotch brite (green side), red nylon pad for a cleaning machine.

Clean tools: Soapy water

Coverage Rate: Undiluted:

Approximately 50 - 80 ml/m², i.e. 1 litre of undiluted PREPARATION CLEANER covers about 12 - 20 m² area per coat. **Diluted:** 1:10 with water covers approximately 200m²
Coats needed: Single application system. For heavily soiled surfaces wash twice.

Drying time: dependent on the ambient temperature and humidity.

Storage: Cool but frost-free. Can be stored for 3 years in unopened containers.

Container sizes: 1 litres, 2.5 litres, 5 litres, 10 litres.

Application for sensitive surfaces:

For surfaces such as linoleum or glossy surfaces try out in an inconspicuous place.

Application for laminate and parquet flooring:

1. Dilute PREPARATION CLEANER, 1 part cleaner to 10 parts water and damp-wipe (not wet).
2. Caution: Too much moisture risks swelling of the timber.

Application for other types of flooring:

1. Apply PREPARATION CLEANER on the previously wetted surface undiluted or diluted (depending on soiling) and if necessary leave for 3 - 5 minutes.
2. Treat possibly with a scotch brite or a red nylon pad and cleaning machine. Do not let PREPARATION CLEANER dry but work in sections, remove all loosened dirt and wipe with clear water.

Replenishing treatment after using Preparation Cleaner:

For professional after treatment we recommend for replenishing with a protection such as Whittle Waxes HARD WAX OIL and follow a maintenance regime as indicated on our website, in the Cleaning, Care and Maintenance section. Whittle Waxes Floor Care should be used for regular cleaning and Whittle Waxes Object Oil when needing minor uplifts and repairs.

Ingredients: Water, <5% anionic surfactants, <5% non-ionic surfactants, <5% phosphates, butyl glycol.



International GHS Safety Notes; P101 If medical advice is needed, keep packaging or label handy. P102 Keep out of the reach of children. P103 Read label before use. Keep away from food and feed. Do not breathe in the spray. Rinse skin and eyes with clean water. In case of skin contact, we recommend wearing suitable gloves (nitrile). Only completely emptied containers may be recycled. Dried residue can be disposed of as household waste or as construction waste. Dispose of liquid residues at a collection point for old paint.

Disclaimer: Our technical advice in written form is given in good faith and on the basis of experiments, but it is only non-binding advice and does not release you from the obligation to test the products supplied by us as to their suitability for the particular purpose. Application, use and processing of the products outside our direct control are entirely your responsibility. Naturally we guarantee consistent quality of our products corresponding to the original sample. With release of new product information the previous information loses validity.

whittle WAXES Factory 13, 25 Quanda Road, Coolum Beach, 4573, QLD, AU Tel: 1300 326 929 info@whittlewaxes.com.au

www.whittlewaxes.com.au