

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) No 453/2010

Article No.: 07239.1  
Print date: 04.11.2013  
Version: 6.0

PNZ Object oil  
Revision date: 22.10.2013  
Issue date: 22.10.2013

EN  
Page 1 / 7

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifiers

Article No. (manufacturer/supplier) 07239.1  
Identification of the substance or mixture PNZ Objectoil

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

### 1.3. Details of the supplier of the safety data sheet

#### supplier (manufacturer/importer/downstream user/distributor)

WHITTLEWAXES Pty Ltd.

Factory 13, 25 Quanda Road,  
Coolum Beach  
QLD 4573,  
Australia

Telephone no. + 6 1 0 7 5 4 7 1 7 9 6 3

E-mail address [info@whittlewaxes.com.au](mailto:info@whittlewaxes.com.au)  
Emergency contact +61 1300 326 929

#### Dept. responsible for information:

Sale

1.4. E-mail (competent person)  
[info@whittlewaxes.com.au](mailto:info@whittlewaxes.com.au)

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

#### Classification according to Directive 67/548/EEC or 1999/45/EC

This mixture is classified as not hazardous according to 1999/45/EC.

### 2.2. Label elements

#### Labelling (67/548/EEC or 1999/45/EC)

##### Hazard statements

n.a.

##### Precautionary statements

51 Use only in well-ventilated areas.  
23 Do not breathe vapour.  
2 Keep out of reach of children.

##### contains:

n.a.

##### Special provisions concerning the labelling of certain mixtures

99 Contains 2-butanone oxime. May produce an allergic reaction.

### 2.3. Other hazards

## SECTION 3: Composition / information on ingredients

### 3.2. Mixtures

#### Product description / chemical characterization

Description Solvent-borne paints

#### Hazardous ingredients

#### Classification according to Directive 67/548/EEC or 1999/45/EC

EC No.	REACH No.	Wt %
CAS No.	Chemical name	Remark
INDEX No.	classification:	
918-481-9	01-2119457273-39-XXXX	
64742-48-9	Kohlenwasserstoffe, C10-C13, n-Alkane, iso-Alkane, cyclische Verbindungen, <2% Aromaten Xn; R65 / R66	25 - 50
265-150-3		
64742-48-9	Naphtha (petroleum), hydrotreated heavy	12,5 - 20
649-327-00-6	Xn; R65	

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) No 453/2010

Article No.: 07239.1 PNZ Object oil  
Print date: 04.11.2013 Revision date: 22.10.2013  
Version: 6.0 Issue date: 22.10.2013

EN  
Page 2 / 7

205-250-6 136-52-7	01-2119524678-29-XXXX Cobaltbis(2-ethylhexanoat) R43/ N; R50-53/ Repr.Cat.3; R62	< 0,5
-----------------------	--	-------

## Additional information

Full text of R-phrases: see section 16.

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### General information

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

#### After inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

#### Following skin contact

Remove contaminated, saturated clothing immediately. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

#### After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

#### After ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do not induce vomiting.

### 4.2. Most important symptoms and effects, both acute and delayed

In all cases of doubt, or when symptoms persist, seek medical advice.

### 4.3. Indication of any immediate medical attention and special treatment needed

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

#### Suitable extinguishing media

alcohol resistant foam, carbon dioxide, Powder, spray mist, (water)

#### Extinguishing media which must not be used for safety reasons:

strong water jet

### 5.2. Special hazards arising from the substance or mixture

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

### 5.3. Advice for firefighters

Provide a conveniently located respiratory protective device. Cool closed containers that are near the source of the fire. Do not allow water used to extinguish fire to enter drains, ground or waterways. Treat runoff as hazardous.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Keep away from sources of ignition. Ventilate affected area. Do not breathe vapours. See protective measures under point 7 and 8.

### 6.2. Environmental precautions

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

### 6.3. Methods and material for containment and cleaning up

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see chapter 13). Clean using cleansing agents. Do not use solvents.

### 6.4. Reference to other sections

Observe protective provisions (see chapter 7 and 8).

## SECTION 7: Handling and storage

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) No 453/2010

Article No.: 07239.1 PNZ Object oil  
Print date: 04.11.2013 Revision date: 22.10.2013  
Version: 6.0 Issue date: 22.10.2013

EN  
Page 3 / 7

Due to the content of organic solvents in the preparation:

## 7.1. Precautions for safe handling

### Advices on safe handling

Avoid formation of flammable and explosive vapour concentrations in the air and exceeding the exposure limit values. Only use the material in places where open light, fire and other flammable sources can be kept away. Electrical equipment must be protected meeting the accepted standard. Keep away from heat sources, sparks and open flames. Use only spark proof tools. Avoid contact with skin, eyes and clothes. Do not inhale dusts, particulates and spray mist when using this preparation. Avoid respiration of swarf. When using do not eat, drink or smoke. Personal protection equipment: refer to chapter 8. Do not empty containers with pressure - no pressure vessel! Always keep in containers that correspond to the material of the original container. Follow the legal protection and safety regulations.

### Precautions against fire and explosion:

Vapours are heavier than air. Vapours form explosive mixtures with air.

## 7.2. Conditions for safe storage, including any incompatibilities

### Requirements for storerooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks. Soils have to conform to the "Guidelines for avoidance of ignition hazards due to electrostatic charges (BGR 132)".

### Hints on joint storage

Keep away from strongly acidic and alkaline materials as well as oxidizers.

### Further information on storage conditions

Take care of instructions on label. Store in a well-ventilated and dry room at temperatures between 15 °C and 30 °C. Protect from heat and direct sunlight. Keep container tightly closed. Remove all sources of ignition. Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

## 7.3. Specific end use(s)

Observe technical data sheet. Observe instructions for use.

## SECTION 8: Exposure controls/personal protection

## 8.1. Control parameters

### Occupational exposure limit values:

Cobaltbis(2-ethylhexanoat)  
EC No. 205-250-6 / CAS No. 136-52-7  
TWA: 0,1 mg/m<sup>3</sup>

### Additional information

TWA : long-term occupational exposure limit value  
STEL : short-term occupational exposure limit value  
Ceiling : peak limitation

## 8.2. Exposure controls

Provide good ventilation. This can be achieved with local or room suction. If this should not be sufficient to keep aerosol and solvent vapour concentration below the exposure limit values, a suitable respiratory protection must be used.

### Occupational exposure controls

#### Respiratory protection

If concentration of solvents is beyond the occupational exposure limit values, approved and suitable respiratory protection must be used. Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190). Use only respiratory protection equipment with CE-symbol including four digit test number.

#### Dand protection

For prolonged or repeated handling the following glove material must be used: z.B. Nitrilkautschuk (nach DIN EN 374)  
Thickness of the glove material > 0,4 mm ; Breakthrough time (maximum wearing time) > 480 min.

Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles DIN EN 374

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

#### Eye protection

Wear closely fitting protective glasses in case of splashes.

#### Protective clothing

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) No 453/2010

Article No.: 07239.1  
Print date: 04.11.2013  
Version: 6.0

PNZ Object oil  
Revision date: 22.10.2013  
Issue date: 22.10.2013

EN  
Page 4 / 7

Wear antistatic clothing of natural fibers (cotton) or heat resistant synthetic fibers.

## Protective measures

After contact clean skin thoroughly with water and soap or use appropriate cleanser.

## Environmental exposure controls

Do not allow to enter into surface water or drains. See chapter 7. No additional measures necessary.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

#### Appearance:

**Physical state** liquid  
**Colour** refer to label  
**Odour** Weak, characteristic

Safety relevant basis data	Unit	Method	Remark
Flash point(°C):	> 67 °C	EN ISO 1523	
Ignition temperature in °C:	200 °C	DIN 51794	
lower explosion limit:	0,6 Vol-%	calculated	
Upper explosion limit:	7,0 Vol-%	calculated	
Vapour pressure at 20 °C:	0,50 mbar	calculated	
Density at 20 °C:	0,858 g/cm <sup>3</sup>	DIN 53217	
Water solubility (g/L):	insoluble		
pH value at 20 °C:	-		
Viscosity at 20 °C:	16 s 4 mm	DIN 53211	
Solid content (%):	34 Wt %		
solvent content:			
Organic solvents:	66 Wt %		
Water:	0 Wt %		

### 9.2. Other information

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

### 10.2. Chemical stability

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to chapter 7.

### 10.3. Possibility of hazardous reactions

Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.

### 10.4. Conditions to avoid

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to chapter 7. Hazardous decomposition byproducts may form with exposure to high temperatures.

### 10.5. Incompatible materials

### 10.6. Hazardous decomposition products

Hazardous decomposition byproducts may form with exposure to high temperatures, e.g.: carbon dioxide, carbon monoxide, smoke, nitrogen oxides.

## SECTION 11: Toxicological information

No data on preparation itself available.

### 11.1. Information on toxicological effects

#### Acute toxicity

oral, LD50, Rat: > 8000 mg/kg  
dermal, LD50, Rabbit: > 4000 mg/kg  
inhalative (vapours), LC50, Rat: > 5,4 mg/L (4 h)

#### Irritant and corrosive effects

Skin (4 h)  
Prolonged or repeated skin contact may cause removal of natural fat from the skin resulting in dermatitis (skin inflammation).  
Eyes  
slightly irritant but not relevant for classification.

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) No 453/2010

Article No.: 07239.1  
Print date: 04.11.2013  
Version: 6.0

PNZ Object oil  
Revision date: 22.10.2013  
Issue date: 22.10.2013

EN  
Page 5 / 7

## Sensitisation

Skin:  
not sensitising.  
Respiratory system:  
not sensitising.

## Specific target organ toxicity

Specific target organ toxicity (single exposure):  
No data available  
Specific target organ toxicity (single exposure), Irritation:  
No data available  
Specific target organ toxicity (single exposure), dizziness:  
No data available  
Specific target organ toxicity (repeated exposure):  
No data available

## Aspiration hazard

Aspiration hazard; evaluation May be fatal if swallowed and enters airways.

## CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Germ cell mutagenicity  
No data available  
Carcinogenicity  
No data available  
Reproductive toxicity  
No data available

## Practical experience/human evidence

Other observations:

Inhaling of solvent components above the MWC-value can lead to health damage, e.g. irritation of the mucous membrane and respiratory organs, as well as damage to the liver, kidneys and the central nerve system. Indications for this are: headache, dizziness, fatigue, amyosthenia, dizziness, in serious cases: unconsciousness. Solvents may cause some of the aforementioned effects through skin resorption. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

## Overall Assessment on CMR properties

The ingredients in this preparation do not meet the criteria for classification as CMR category 1 or 2. according to 67/548/EEC.

There is no information available on the preparation itself . The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and has not been classified.

## SECTION 12: Ecological information

### overall evaluation

There is no information available on the preparation itself .  
Do not allow to enter into surface water or drains.

#### 12.1. Toxicity

Fish toxicity, LC50: (96 h)  
No data available  
Daphnia toxicity, EC50: (48 h)  
No data available  
Algae toxicity, ErC50:  
No data available

### Long-term Ecotoxicity

Fish toxicity, LC50: (96 h)  
No data available  
Daphnia toxicity, EC50: (48 h)  
No data available  
Algae toxicity, ErC50:  
No data available

#### 12.2. Persistence and degradability

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) No 453/2010

Article No.: 07239.1  
Print date: 04.11.2013  
Version: 6.0

PNZ Object oil  
Revision date: 22.10.2013  
Issue date: 22.10.2013

EN  
Page 6 / 7

:  
Biodegradable.

## 12.3. Bioaccumulative potential

Distribution coefficient (n-octanol/ water) (log P O/W):  
No data available

### Bioconcentration factor (BCF)

Bioconcentration factor(BCF):  
No data available

## 12.4. Mobility in soil

:  
No data available

## 12.5. Results of PBT assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

## 12.6. Other adverse effects

The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and is not classified as dangerous for the environment.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

#### Appropriate disposal / Product Recommendation

Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Waste disposal according to EC directives 75/442/EEC and 91/689/EEC in the corresponding versions, covering waste and dangerous waste.

#### List of proposed waste codes/waste designations in accordance with EWC

080112 waste paint and varnish other than those mentioned in 080111

#### packaging

#### Recommendation

Non-contaminated packages may be recycled. Vessels not properly emptied are special waste.

## SECTION 14: Transport information

**No dangerous good in sense of this transport regulation.**

### 14.1. UN number

n.a.

### 14.2. UN proper shipping name

### 14.3. Transport hazard class(es)

n.a.

### 14.4. Packing group

n.a.

### 14.5. Environmental hazards

Land transport(ADR/RID)

n.a.

Marine pollutant

n.a.

### 14.6. Special precautions for user

Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage.

Advices on safe handling: see parts 6 - 8

#### Additional information

#### Land transport(ADR/RID)

tunnel restriction code

-

#### Sea transport(IMDG)

EmS-No.

n.a.

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) No 453/2010

Article No.: 07239.1 PNZ Object oil  
Print date: 04.11.2013 Revision date: 22.10.2013 EN  
Version: 6.0 Issue date: 22.10.2013 Page 7 / 7

- 14.7. **Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**  
not applicable

## SECTION 15: Regulatory information

- 15.1. **Safety, health and environmental regulations/legislation specific for the substance or mixture**

### EU legislation

#### Information according to 1999/13/EC about limitation of emissions of volatile organic compounds (VOC-guideline).

VOC-value (in g/L) ISO 11890-2: 564,085

VOC-value (in g/L) ASTM D 2369: 564,085

#### according to EU-regulation 2004/42/EC (appendix II)

EU limit value for this product (cat. (Cat. A/f)): 700 g/l (2007)/700 g/l (2010).

This product contains max 564,085 g/l VOC.

### National regulations

#### Restrictions of occupation

Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.  
Observe restrictions to employment for juvenils according to the "juvenile work protection guideline" (94/33/EC).

#### Other regulations, restrictions and prohibition regulations

- 15.2. **Chemical Safety Assessment**

For the following substances of this preparation a chemical safety assessment has been carried out:

EC No. CAS No.	Chemical name	REACH No.
205-250-6 136-52-7	Cobaltbis(2-ethylhexanoat)	01-2119524678-29-XXXX

## SECTION 16: Other information

### Wording of the R-phrases under paragraph 3:

Xn; R65 R66	Harmful	Harmful: may cause lung damage if swallowed. Repeated exposure may cause skin dryness or cracking.
R43 N; R50-53	Dangerous for the environment	May cause sensitization by skin contact. Very toxic to aquatic life. May cause long-term adverse effects in the aquatic environment.
Repr. Cat. 3; R62	Reproductive toxic Cat. 3 (Repr. Cat. 3)	Possible risk of impaired fertility.

### Additional information

The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and EU regulations. Without written approval, the product must not be used for purposes different from those mentioned in chapter 1. It is always the user's duty to take any necessary measures for meeting the requirements laid down by local rules and regulations. The details in this safety data sheet describe the safety requirements of our product and are not to be regarded as guaranteed attributes of the product.