

Trade name: Treatex Slate Colour Tone 11050Z

Version: 13 / WORLD

Date created/revised: 03.11.16

Replaces Version: 12 / WORLD

Print date: 16.08.16

## 1. Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Treatex Slate Colour Tone 11050Z

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/preparation

Surface treatment of wood and other materials

#### Identified Uses

	-----
SU22	REACHSET 2003 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
ERC8a	Wide dispersive indoor use of processing aids in open systems
ERC8c	Wide dispersive indoor use resulting in inclusion into or onto a matrix
PROC10	Roller application or brushing

### 1.3. Details of the supplier of the safety data sheet

#### Producer

Whittle Waxes  
Factory 13, 25 Quanda Road  
Coolum Beach, 4573 QLD AU  
Telephone no. +61 (0) 1300 326 929 or 07 5471 7963  
E-mail address info@whittlewaxes.com.au

### 1.4. Emergency telephone number

Australia +61 13 11 26

## 2. Hazards identification

### 2.1. Classification of the substance or mixture

#### Classification (Regulation (EC) No. 1272/2008)

Classification (Regulation (EC) No. 1272/2008)  
Flam. Liq. 3 H226  
STOT SE 3 H336

The product is classified and labelled in accordance with Regulation (EC) No 1272/2008  
For explanation of abbreviations see section 16.

### 2.2. Label elements

#### Labelling according to regulation (EC) No 1272/2008

#### Hazard pictograms



#### Signal word

Warning

Trade name: Treatex Slate Colour Tone 11050Z

Version: 13 / WORLD

Date created/revised: 03.11.16

Replaces Version: 12 / WORLD

Print date: 16.08.16

### Hazard statements

H226 Flammable liquid and vapour.  
H336 May cause drowsiness or dizziness.

### Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.  
P280 Wear protective gloves/protective clothing/eye protection/face protection.  
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P309+P315 IF exposed or if you feel unwell: Get immediate medical advice/attention.  
P403+P233 Store in a well-ventilated place. Keep container tightly closed.

### Hazardous component(s) to be indicated on label (Regulation (EC) No. 1272/2008)

contains naphtha hydrodesulfurized heavy

### Supplemental information

EUH066 Repeated exposure may cause skin dryness or cracking.

### Further supplemental information

Cleaning cloth soaked with the product can self ignite during packing up, therefore dry the cloth on a line or through spreading and dispose of after dry up.

### 2.3. Other hazards

This mixture contains no substance considered to be persistent, bioaccumulating nor toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB) (if not listed in Section 3).

## 3. Composition/information on ingredients

### Hazardous ingredients (Regulation (EC) No. 1272/2008)

#### naphtha hydrodesulfurized heavy

CAS No. 64742-48-9  
EINECS no. 265-150-3  
Registration no. 01-2119463258-33  
Concentration >= 25 < 50 %

Classification (Regulation (EC) No. 1272/2008)

Flam. Liq. 3 H226  
Asp. Tox. 1 H304  
STOT SE 3 H336

#### alkanes, C11-14-iso-

CAS No. 90622-58-5  
Concentration >= 10 < 25 %

Classification (Regulation (EC) No. 1272/2008)

Asp. Tox. 1 H304  
Aquatic Chronic 4 H413  
EUH066

#### naphtha hydrodesulfurized heavy

CAS No. 64742-48-9  
EINECS no. 265-150-3

Trade name: Treatex Slate Colour Tone 11050Z

Version: 13 / WORLD

Date created/revised: 03.11.16

Replaces Version: 12 / WORLD

Print date: 16.08.16

Registration no. 01-2119457273-39  
Concentration  $\geq$  1 < 10 %

Classification (Regulation (EC) No. 1272/2008)  
Asp. Tox. 1 H304  
EUH066

#### 2-ethylhexanoic acid zirconium salt

CAS No. 22464-99-9  
EINECS no. 245-018-1  
Registration no. 01-2119979088-21  
Concentration  $\geq$  0,1 < 1 %

Classification (Regulation (EC) No. 1272/2008)  
Repr. 2 H361d

#### N-alkyl propylene diamine dioleate

CAS No. 40027-38-1  
EINECS no. 254-754-2  
Concentration  $\geq$  0,1 < 1 %

Classification (Regulation (EC) No. 1272/2008)  
Acute Tox. 4 H302  
Skin Irrit. 2 H315  
Eye Dam. 1 H318  
Aquatic Acute 1 H400  
Route of exposure: Oral exposure

#### Further hazardous ingredients

For explanation of abbreviations see section 16.

This product does not contain substances of very high concern (Regulation (EC) No 1907/2006 (REACH), Article 57) (if not listed in Section 3).

## 4. First aid measures

### 4.1. Description of first aid measures

#### General information

When symptoms persist or in all cases of doubt seek medical advice. If unconscious place in recovery position and seek medical advice. First aider needs to protect himself. Move out of dangerous area.

#### After inhalation

In case of accident by inhalation: remove casualty to fresh air and keep at rest. Keep patient warm and at rest. Consult a physician for severe cases.

#### After skin contact

Wash off immediately with soap and plenty of water. Do NOT use solvents or thinners. If skin irritation persists, call a physician.

#### After eye contact

In case of eye contact, remove contact lens and rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Consult a physician.

#### After ingestion

Do NOT induce vomiting. Consult a physician.

Trade name: Treatex Slate Colour Tone 11050Z

Version: 13 / WORLD

Date created/revised: 03.11.16

Replaces Version: 12 / WORLD

Print date: 16.08.16

#### **4.2. Most important symptoms and effects, both acute and delayed**

Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. High concentration of vapours may cause irritation to eyes and respiratory system and produce narcotic effects. The liquid splashed in the eyes may cause irritation and reversible damage.

#### **4.3. Indication of any immediate medical attention and special treatment needed**

##### **Hints for the physician / treatment**

Treat symptomatically.

### **5. Firefighting measures**

#### **5.1. Extinguishing media**

##### **Suitable extinguishing media**

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

##### **Non suitable extinguishing media**

Do not use a solid water stream as it may scatter and spread fire.

#### **5.2. Special hazards arising from the substance or mixture**

As the product contains combustible organic components, fire will produce dense black smoke containing hazardous products of combustion (see section 10). Exposure to decomposition products may be a hazard to health. Vapours can form an explosive mixture with air.

#### **5.3. Advice for firefighters**

##### **Special protective equipment for fire-fighting**

Wear self contained breathing apparatus for fire fighting if necessary.

##### **Other information**

Do not allow run-off from fire fighting to enter drains or water courses. Cool closed containers exposed to fire with water spray. Standard procedure for chemical fires.

### **6. Accidental release measures**

#### **6.1. Personal precautions, protective equipment and emergency procedures**

Remove all sources of ignition. Ensure adequate ventilation. Avoid breathing vapours, mist or gas.

#### **6.2. Environmental precautions**

Do not flush into surface water or sanitary sewer system. Avoid subsoil penetration. Contact the proper local authorities.

#### **6.3. Methods and material for containment and cleaning up**

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Clean contaminated floors and objects thoroughly while observing environmental regulations. Clean with detergents. Avoid solvents. Keep in suitable, closed containers for disposal.

#### **6.4. Reference to other sections**

Refer to protective measures listed in sections 7 and 8.

### **7. Handling and storage**

#### **7.1. Precautions for safe handling**

Trade name: Treatex Slate Colour Tone 11050Z

Version: 13 / WORLD

Date created/revised: 03.11.16

Replaces Version: 12 / WORLD

Print date: 16.08.16

### Advice on safe handling

Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. Keep container tightly closed and dry in a cool, well-ventilated place. Use only with adequate ventilation/personal protection. Ensure adequate ventilation. Provide for sufficient ventilation. This can be achieved by local exhaust or general exhaust air collection. Wear a suitable respirator if the ventilation is not sufficient to keep the solvent vapour concentration below the occupational limit values. Avoid contact with skin and eyes. Do not breathe vapours or spray mist. Do not eat, drink or smoke when using this product. Use personal protective equipment. For personal protection see Section 8.

### Advice on protection against fire and explosion

Vapours may form explosive mixtures with air. Vapours are heavier than air and may spread along floors. In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Mixture may charge electrostatically: always use earthing leads when transferring from one container to another. Take measures to prevent the build up of electrostatic charge. Wear shoes with conductive soles. No sparking tools should be used. Standard procedure for chemical fires. Do not process in the same cabin together with highly flammable material (e.g. CN lacquer) => fire hazard through self ignition! Cleaning cloth soaked with the product can self ignite during packing up, therefore dry the cloth on a line or through spreading and dispose of after dry up.

## 7.2. Conditions for safe storage, including any incompatibilities

### Requirements for storage rooms and vessels

Keep in an area equipped with solvent resistant flooring. Store at room temperature in the original container. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

### Hints on storage assembly

Keep away from oxidising agents and strongly acid or alkaline materials.

### Storage class according to the Occupation Safety Ordinance:

Flammable.

### Further information on storage conditions

Keep away from heat. Protect from sunlight. Protect from frost - <10%, for a solvent content (see section 15 VOC). Keep away from sources of ignition - No smoking. Store in accordance with the particular national regulations.

## 7.3. Specific end use(s)

See exposure scenario, if available.

## 8. Exposure controls/personal protection

### 8.1. Control parameters

#### Other information

-

#### Derived No/Minimal Effect Levels (DNEL/DMEL)

##### naphtha hydrodesulfurized heavy

Type of value	DNEL	
Reference group	Workers (professional)	
Duration of exposure	Long-term	
Route of exposure	Dermal exposure	
Mode of action	systemic effect	
Concentration	300	mg/kg/d

Trade name: Treatex Slate Colour Tone 11050Z

Version: 13 / WORLD

Date created/revised: 03.11.16

Replaces Version: 12 / WORLD

Print date: 16.08.16

Type of value	DNEL	
Reference group	Workers (professional)	
Duration of exposure	Long-term	
Route of exposure	inhalative	
Mode of action	systemic effect	
Concentration	1500	mg/m <sup>3</sup>
Type of value	DNEL	
Reference group	Consumers	
Duration of exposure	Long-term	
Route of exposure	Dermal exposure	
Mode of action	systemic effect	
Concentration	300	mg/kg/d
Type of value	DNEL	
Reference group	Consumers	
Duration of exposure	Long-term	
Route of exposure	inhalative	
Mode of action	systemic effect	
Concentration	900	mg/m <sup>3</sup>
Type of value	DNEL	
Reference group	Consumers	
Duration of exposure	Long-term	
Route of exposure	Oral exposure	
Mode of action	systemic effect	
Concentration	300	mg/kg/d
<b>naphtha hydrodesulfurized heavy</b>		
Type of value	DNEL	
Reference group	Workers (industrial)	
Duration of exposure	Long-term	
Route of exposure	Dermal exposure	
Mode of action	systemic effect	
Concentration	208	mg/kg/d
Type of value	DNEL	
Reference group	Workers (industrial)	
Duration of exposure	Long-term	
Route of exposure	inhalative	
Mode of action	systemic effect	
Concentration	871	mg/m <sup>3</sup>
Type of value	DNEL	
Reference group	Consumers	
Duration of exposure	Long-term	
Route of exposure	Oral exposure	
Mode of action	systemic effect	
Concentration	125	mg/kg/d
Type of value	DNEL	
Reference group	Consumers	
Duration of exposure	Long-term	

Trade name: Treatex Slate Colour Tone 11050Z

Version: 13 / WORLD

Date created/revised: 03.11.16

Replaces Version: 12 / WORLD

Print date: 16.08.16

Route of exposure	Dermal exposure	
Mode of action	systemic effect	
Concentration	125	mg/kg/d
Type of value	DNEL	
Reference group	Consumers	
Duration of exposure	Long-term	
Route of exposure	inhalative	
Mode of action	systemic effect	
Concentration	900	mg/m <sup>3</sup>

## 8.2. Exposure controls

### Exposure controls

Apply technical measures to comply with the workplace exposure limits. Provide for sufficient ventilation. This can be achieved by local exhaust or general exhaust air collection. Wear a suitable respirator if the ventilation is not sufficient to keep the solvent vapour concentration below the occupational limit values.

### Respiratory protection

In case of mist, spray or aerosol exposure wear suitable personal respiratory protection and protective suit. Recommended Filter type: Combination filter: A2-P2 (EN 141, 143, 371)

### Hand protection

Protective gloves complying with EN 374.

Glove material

Multilayer gloves made from

Appropriate Material Fluorinated rubber / butyl-rubber

This recommendation is valid only for the product named in this safety data sheet supplied by us, and only for the indicated intended use purposes.

The exact break through time can be obtained from the protective glove producer and this has to be observed.

Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.

### Eye protection

Wear eye glasses with side protection according to EN 166.

### Body protection

Wear suitable protective clothing. Remove contaminated clothing and wash it before reuse. Wash hands before breaks and after work.

## 9. Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

<b>Form</b>	liquid
<b>Colour</b>	dark grey
<b>Odour</b>	characteristic
<b>Odour threshold</b>	
Remarks	no data available
<b>pH value</b>	
Remarks	no data available
<b>Melting point</b>	
Remarks	no data available

Trade name: Treatex Slate Colour Tone 11050Z

Version: 13 / WORLD

Date created/revised: 03.11.16

Replaces Version: 12 / WORLD

Print date: 16.08.16

**Freezing point**

Remarks no data available

**Initial boiling point and boiling range**

Value 180 to 217 °C

**Flash point**

Value 36 to 55 °C

**Evaporation rate**

Remarks no data available

**Flammability (solid, gas)**

no data available

**Upper/lower flammability or explosive limits**

Remarks no data available

**Vapour density**

Remarks no data available

**Density**

Value 0,92 g/cm<sup>3</sup>  
 Temperature 20 °C

**Solubility in water**

Remarks no data available

**Solubility(ies)**

Remarks no data available

**Partition coefficient: n-octanol/water**

Remarks no data available

**Ignition temperature**

Remarks no data available

**Decomposition temperature**

Remarks no data available

**Viscosity**

**kinematic**

Value > 21 mm<sup>2</sup>/s  
 Temperature 40 °C

**Efflux time**

Value 26 to 32 s  
 Temperature 20 °C  
 Method DIN 53211 4 mm

**Explosive properties**

evaluation no data available

**Oxidising properties**

Remarks no data available

**9.2. Other information**

**Other information**

This information is not available.



Trade name: Treatex Slate Colour Tone 11050Z

Version: 13 / WORLD

Date created/revised: 03.11.16

Replaces Version: 12 / WORLD

Print date: 16.08.16

## 10. Stability and reactivity

### 10.1. Reactivity

No conditions to be specially mentioned.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

To avoid thermal decomposition, do not overheat.

### 10.4. Conditions to avoid

Heat, flames and sparks.

#### Decomposition temperature

Remarks no data available

### 10.5. Incompatible materials

Keep away from oxidising agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

### 10.6. Hazardous decomposition products

Carbon dioxide (CO<sub>2</sub>), carbon monoxide (CO), oxides of nitrogen (NO<sub>x</sub>), dense black smoke. No decomposition if stored and applied as directed.

## 11. Toxicological information

### 11.1. Information on toxicological effects

#### Acute oral toxicity

Remarks Based on available data, the classification criteria are not met.

#### Acute oral toxicity (Components)

##### naphtha hydrodesulfurized heavy

Species	rat		
LD50	>	5000	mg/kg

##### alkanes, C11-14-iso-

Species	rat		
LD50	>	5000	mg/kg
Method	OECD 401		

##### naphtha hydrodesulfurized heavy

Species	rat		
LD50	>	5000	mg/kg

#### Acute dermal toxicity

Remarks Based on available data, the classification criteria are not met.

#### Acute dermal toxicity (Components)

##### naphtha hydrodesulfurized heavy

Species	rat		
LD50		3160	mg/kg

##### alkanes, C11-14-iso-

Species	rabbit		
LD50	>	5000	mg/kg

Trade name: Treatex Slate Colour Tone 11050Z

Version: 13 / WORLD

Date created/revised: 03.11.16

Replaces Version: 12 / WORLD

Print date: 16.08.16

**naphtha hydrodesulfurized heavy**

Species rabbit  
LD50 > 3000 mg/kg

**Acute inhalational toxicity**

Remarks Based on available data, the classification criteria are not met.

**Acute inhalative toxicity (Components)**

**naphtha hydrodesulfurized heavy**

Species rat  
LC50 appr. 100 mg/l  
Duration of exposure 4 h  
Remarks Mist

**alkanes, C11-14-iso-**

Species rat  
LC50 > 5,6 mg/l  
Duration of exposure = 4 h  
Remarks Mist

**naphtha hydrodesulfurized heavy**

LC50 > 5 mg/l  
Duration of exposure 4 h  
Remarks Mist

**Skin corrosion/irritation**

Remarks Based on available data, the classification criteria are not met.

**Serious eye damage/irritation**

Remarks Based on available data, the classification criteria are not met.

**Sensitization**

Remarks Based on available data, the classification criteria are not met.

**Sensitization (Components)**

**uaternary ammonium compounds, benzyl(hydrogenated tallow alkyl)dimethyl, stearates, salts with bentonite**

evaluation No sensitizing effects known.

**Mutagenicity**

Remarks Based on available data, the classification criteria are not met.

**Reproductive toxicity**

Remarks Based on available data, the classification criteria are not met.

**Carcinogenicity**

Remarks Based on available data, the classification criteria are not met.

**Specific Target Organ Toxicity (STOT)**

Remarks The classification criteria are met

**Aspiration hazard**

Based on available data, the classification criteria are not met.

**Other information**

No data is available on the product itself.

**12. Ecological information**

Trade name: Treatex Slate Colour Tone 11050Z

Version: 13 / WORLD

Date created/revised: 03.11.16

Replaces Version: 12 / WORLD

Print date: 16.08.16

## 12.1. Toxicity

### General information

No data is available on the product itself.

### Fish toxicity (Components)

#### naphtha hydrodesulfurized heavy

Species	Pimephales promelas (fathead minnow)		
LC50	2200		mg/l
Duration of exposure	96	h	

#### naphtha hydrodesulfurized heavy

Species	Pimephales promelas (fathead minnow)		
NOEC	2,6		mg/l
Duration of exposure	14	d	

#### naphtha hydrodesulfurized heavy

Species	Oncorhynchus mykiss (rainbow trout)		
LC50	16		mg/l
Duration of exposure	96	h	

### Daphnia toxicity (Components)

#### naphtha hydrodesulfurized heavy

Species	Chaetogammarus marinus		
EC50	2,6		mg/l
Duration of exposure	96	h	

#### alkanes, C11-14-iso-

Species	Daphnia magna (Water flea)		
EC50	> 1000		mg/l
Duration of exposure	48	h	

#### naphtha hydrodesulfurized heavy

Species	Daphnia magna (Water flea)		
EC50	4,5		mg/l
Duration of exposure	48	h	

#### naphtha hydrodesulfurized heavy

Species	Daphnia magna (Water flea)		
NOEC	2,6		mg/l
Duration of exposure	21	d	

### Algae toxicity (Components)

#### naphtha hydrodesulfurized heavy

Species	Pseudokirchneriella subcapitata (green algae)		
EC50	3,1		mg/l
Duration of exposure	72	h	

## 12.2. Persistence and degradability

### General information

No data is available on the product itself.

### Biodegradability (Components)

#### alkanes, C11-14-iso-

evaluation	Not readily biodegradable.		
------------	----------------------------	--	--

#### naphtha hydrodesulfurized heavy

Value	77,05		%
-------	-------	--	---

Trade name: Treatex Slate Colour Tone 11050Z

Version: 13 / WORLD

Date created/revised: 03.11.16

Replaces Version: 12 / WORLD

Print date: 16.08.16

Duration of test evaluation 28 d  
Readily biodegradable.

### 12.3. Bioaccumulative potential

#### General information

No data is available on the product itself.

#### Partition coefficient: n-octanol/water

Remarks no data available

### 12.4. Mobility in soil

#### General information

No data is available on the product itself.

#### Mobility in soil

no data available

### 12.5. Results of PBT and vPvB assessment

#### General information

Not applicable

### 12.6. Other adverse effects

#### General information

No data is available on the product itself.

#### General information / ecology

No data is available on the product itself.

## 13. Disposal considerations

### 13.1. Waste treatment methods

#### Disposal recommendations for the product

EWC waste code 080111 - waste paint and varnish containing organic solvents or other dangerous substances  
EWC waste code 200127 - paint, inks, adhesives and resins containing dangerous substances

Where possible recycling is preferred to disposal or incineration.  
Try to prevent the material from entering drains or water courses.

#### modified product

EWC waste code 080113 - sludges from paint or varnish containing organic solvents or other dangerous substances  
EWC waste code 080115 - aqueous sludges containing paint or varnish containing organic solvents or other dangerous substances

#### Dried residues

EWC waste code 080112 - waste lacquers and waste paint except those falling under 080111

#### Disposal recommendations for packaging

EWC waste code 150110 - packaging containing residues of or contaminated by dangerous substances

Empty remaining contents.  
Empty containers should be taken to local recyclers for disposal.

Trade name: Treatex Slate Colour Tone 11050Z

Version: 13 / WORLD

Date created/revised: 03.11.16

Replaces Version: 12 / WORLD

Print date: 16.08.16

## 14. Transport information

### Land transport ADR/RID

**14.1. UN number**

UN 1263

**14.2. UN proper shipping name**

PAINT

**14.3. Transport hazard class(es)**

Class 3

Label 3

**14.4. Packing group**

Packing group III

Special provision 640E

Limited Quantity 5I

Transport category 3

Tunnel restriction code D/E

### Marine transport IMDG/GGVSee

**14.1. UN number**

UN 1263

**14.2. UN proper shipping name**

PAINT

**14.3. Transport hazard class(es)**

Class 3

**14.4. Packing group**

Packing group III

### Air transport ICAO/IATA

**14.1. UN number**

UN 1263

**14.2. UN proper shipping name**

PAINT

**14.3. Transport hazard class(es)**

Class 3

**14.4. Packing group**

Packing group III

## 15. Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

**VOC**

VOC (EU) 51,5 % 476 g/l

**Non-volatile content**

Value [%] 47,4

### 15.2. Chemical safety assessment

For this substance / mixture a chemical safety assessment was not carried out.

## 16. Other information

**Hazard statements listed in Chapter 3**

Trade name: Treatex Slate Colour Tone 11050Z

Version: 13 / WORLD

Date created/revised: 03.11.16

Replaces Version: 12 / WORLD

Print date: 16.08.16

EUH066	Repeated exposure may cause skin dryness or cracking.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H336	May cause drowsiness or dizziness.
H361d	Suspected of damaging the unborn child.
H400	Very toxic to aquatic life.
H413	May cause long lasting harmful effects to aquatic life.

### CLP categories listed in Chapter 3

Acute Tox. 4	Acute toxicity, Category 4
Aquatic Acute 1	Hazardous to the aquatic environment, acute, Category 1
Aquatic Chronic 4	Hazardous to the aquatic environment, chronic, Category 4
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Dam. 1	Serious eye damage, Category 1
Flam. Liq. 3	Flammable liquid, Category 3
Repr. 2	Reproductive toxicity, Category 2
Skin Irrit. 2	Skin irritation, Category 2
STOT SE 3	Specific target organ toxicity - single exposure, Category 3

### Abbreviations

ADR - Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID - Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IMDG - International Maritime Code for Dangerous Goods

IATA - International Air Transport Association

IATA-DGR - Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO-TI - Technical Instructions by the "International Civil Aviation Organization" (ICAO)

GHS - Globally Harmonized System of Classification and Labelling of Chemicals

EINECS - European Inventory of Existing Commercial Chemical Substances

CAS - Chemical Abstracts Service (division of the American Chemical Society)

GefStoffV - Gefahrstoffverordnung (Ordinance on Hazardous Substances, Germany)

LOAEL - Lowest Observed Adverse Effect Level

LOEL - Lowest Observed Effect Level

NOAEL - No Observed Adverse Effect Level

NOEC - No Observed Effect Concentration

NOEL - No Observed Effect Level

OECD - Organisation for Economic Cooperation and Development

VOC - Volatile Organic Compounds

Changes since the last version are highlighted in the margin (\*\*). This version replaces all previous versions.

This safety datasheet only contains information relating to safety and does not replace any product information or product specification.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification.

The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

The information contained herein is based on the present state of our knowledge and does therefore not guarantee certain properties.

Trade name: Treatex Slate Colour Tone 11050Z

Version: 13 / WORLD

Date created/revised: 03.11.16

Replaces Version: 12 / WORLD

Print date: 16.08.16

## **Annex to the extended Safety Data Sheet (eSDS)**

### **Short title of the exposure scenario**

ES026 - Professional uses: roller application or brushing, dipping and pouring and other processing without aerosol formation (inside)

### **Use of the substance/preparation**

Surface treatment of wood and other materials

### **Use**

SU22	Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
ERC8a	Wide dispersive indoor use of processing aids in open systems
ERC8c	Wide dispersive indoor use resulting in inclusion into or onto a matrix
PROCh01	Other processing without aerosol formation
PROC10	Roller application or brushing
PROC13	Treatment of articles by dipping and pouring

## **Contributing exposure scenario controlling environmental exposure**

### **Use**

ERC8a	Wide dispersive indoor use of processing aids in open systems
ERC8c	Wide dispersive indoor use resulting in inclusion into or onto a matrix

### **Physical form**

liquid

### **Hazardous ingredients**

#### **naphtha hydrodesulfurized heavy**

CAS No.	64742-48-9				
EINECS no.	265-150-3				
Registration no.	01-2119463258-33				
Concentration	>= 25	<	50	%	

#### **alkanes, C11-14-iso-**

CAS No.	90622-58-5				
Concentration	>= 10	<	25	%	

#### **naphtha hydrodesulfurized heavy**

CAS No.	64742-48-9				
EINECS no.	265-150-3				
Registration no.	01-2119457273-39				
Concentration	>= 1	<	10	%	

#### **2-ethylhexanoic acid zirconium salt**

CAS No.	22464-99-9				
EINECS no.	245-018-1				
Registration no.	01-2119979088-21				
Concentration	>= 0,1	<	1	%	

#### **N-alkyl propylene diamine dioleate**

CAS No.	40027-38-1				
EINECS no.	254-754-2				
Concentration	>= 0,1	<	1	%	

### **Maximum amount used per time or activity**

Emission days per site:	<=	250
-------------------------	----	-----

### **Other relevant operational conditions**

Safety data sheet in accordance with regulation (EC) No 1907/2006

Trade name: Treatex Slate Colour Tone 11050Z

Version: 13 / WORLD

Date created/revised: 03.11.16

Replaces Version: 12 / WORLD

Print date: 16.08.16

Use: Room temperature  
Drying and through-curing takes place at ambient temperature or at higher temperatures.  
Volatile organic substances will volatilise into the atmospheric air inside.  
Where possible recycling is preferred to disposal or incineration.  
The product should not be allowed to enter drains, water courses or the soil.  
Dispose of rinse water in accordance with local and national regulations.

#### **Waste water**

Do not flush into surface water or sanitary sewer system.

#### **Exhaust air**

Keep container closed. Discharge into the environment must be avoided.

#### **Soil**

Use only in an area equipped with an impervious floor.

#### **Disposal recommendations for the product**

EWC waste code 080111 - waste paint and varnish containing organic solvents or other dangerous substances  
200127 - paint, inks, adhesives and resins containing dangerous substances

Where possible recycling is preferred to disposal or incineration.  
Try to prevent the material from entering drains or water courses.

#### **modified product**

EWC waste code 080113 - sludges from paint or varnish containing organic solvents or other dangerous substances  
080115 - aqueous sludges containing paint or varnish containing organic solvents or other dangerous substances

#### **Dried residues**

EWC waste code 080112 - waste lacquers and waste paint except those falling under 080111

#### **Disposal recommendations for packaging**

EWC waste code 150110 - packaging containing residues of or contaminated by dangerous substances

Empty remaining contents.  
Empty containers should be taken to local recyclers for disposal.

### **Contributing exposure scenario controlling worker exposure (professional)**

#### **Use**

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)  
PROC10 Roller application or brushing  
PROC13 Treatment of articles by dipping and pouring  
PROCh01 Other processing without aerosol formation

#### **Physical form**

liquid

#### **Hazardous ingredients**

##### **naphtha hydrodesulfurized heavy**

CAS No. 64742-48-9  
EINECS no. 265-150-3  
Registration no. 01-2119463258-33  
Concentration >= 25 < 50 %



Trade name: Treatex Slate Colour Tone 11050Z

Version: 13 / WORLD

Date created/revised: 03.11.16

Replaces Version: 12 / WORLD

Print date: 16.08.16

**alkanes, C11-14-iso-**

CAS No. 90622-58-5  
Concentration >= 10 < 25 %

**naphtha hydrodesulfurized heavy**

CAS No. 64742-48-9  
EINECS no. 265-150-3  
Registration no. 01-2119457273-39  
Concentration >= 1 < 10 %

**2-ethylhexanoic acid zirconium salt**

CAS No. 22464-99-9  
EINECS no. 245-018-1  
Registration no. 01-2119979088-21  
Concentration >= 0,1 < 1 %

**N-alkyl propylene diamine dioleate**

CAS No. 40027-38-1  
EINECS no. 254-754-2  
Concentration >= 0,1 < 1 %

**Maximum amount used per time or activity**

Duration of exposure <= 8 h/d  
Frequency of exposure <= 220 d/a

**Other relevant operational conditions**

Use: Room temperature  
Drying and through-curing takes place at ambient temperature or at higher temperatures.  
Volatile organic substances will volatilise into the atmospheric air inside.  
Read attached instructions before use.

**Product substance and product safety related measures**

Apply technical measures to comply with the occupational exposure limits. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL, suitable respiratory protection must be worn.

**Respiratory protection**

In case of mist, spray or aerosol exposure wear suitable personal respiratory protection and protective suit. Recommended Filter type: Combination filter: A2-P2 (EN 141, 143, 371)

**Hand protection**

Protective gloves complying with EN 374.  
Glove material  
Multilayer gloves made from  
Appropriate Material Fluorinated rubber / butyl-rubber  
This recommendation is valid only for the product named in this safety data sheet supplied by us, and only for the indicated intended use purposes.  
The exact break through time can be obtained from the protective glove producer and this has to be observed.  
Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.

**Eye protection**

Wear eye glasses with side protection according to EN 166.

**Body protection**

Wear suitable protective clothing. Remove contaminated clothing and wash it before reuse. Wash hands

Safety data sheet in accordance with regulation (EC) No 1907/2006

Trade name: Treatex Slate Colour Tone 11050Z

Version: 13 / WORLD

Date created/revised: 03.11.16

Replaces Version: 12 / WORLD

Print date: 16.08.16

before breaks and after work.

## **Information on estimated exposure and downstream-user guidance**

### **Guidance for Downstream Users**

The downstream user can evaluate whether he operates within the conditions set in the exposure scenario on the basis of the information supplied. This evaluation can be conducted by an expert or using the risk assessment tools recommended by ECHA.