



whittle
WAXES



Product Information

Whittle Waxes Worktop Oil

Deeply penetrating, water and dirt retardant oil specifically designed for worktops

Properties: An open-pored, moisture regulating oil with high covering power and good penetration that gives wood high-quality surface protection and is water and dirt-retardant

Benefits;

- High covering power
- Good penetration
- High quality protection against water and dirt

Areas of use: For all interior rough and caustic-treated woods.

Usage: Untreated wood must be clean, free of grease and resin and finely sanded, max. Wood moisture 14%. Oil and room temperature must be at least 18°C, max. Humidity 60%. Wood rich in resin should be washed off with *Whittle Waxes DEEP-CLEAN* and allowed to dry for at least 12 hours.

Apply the worktop oil with an oil roller or brush wet-on-wet and repeat rolling until the entire surface remains wet and the wood no longer absorbs oil (up to 60 minutes depending on the type of wood). Then rub in excess oil with a cotton cloth until no more remains.

There must be no shiny patches or oil splashes on the entire surface; it must appear dry. Polish the wooden surface with a cotton cloth after at least 24 hours drying time.

Please note: Solid, composite and veneered woods absorb the oil differently, which may lead to colour differences between them. Oil a test piece!

Clean: with *Whittle Waxes WOODEN-FLOOR-SOAP* application after 7 days! Unused oil can be used for maintenance as required.

Coverage: Dense resinous timbers, approx 100ml/m² per coat, up to 200ml/m² per coat for less dense timbers

Drying Time: approximately 2-3 days. Protect from water during this time. Oxygen and temperature above 18 °C accelerate the drying process. Protect from water during this period! Do not use for at least 2 days, after which time the wood may be used with care. The longevity and preservation of value of oiled surfaces is strongly dependent on careful treatment in the first few days.

Whittle Waxes Victoria 6/9 Pilgrim Court Ringwood VIC 3134 Ph: 03 9873 848

1300 ECOWAX (1300 326 929) info@whittlewaxes.com.au www.whittlewaxes.com.au



whittle
W A X E S



Storage: Recommended storage temperature: Above 8°C.

Colours: Colourless

Note: When using several containers with different lot numbers, mix together in larger container.

Container sizes: 0.75L, 2.5L, 10L.

Ingredients: Natural oils made from: thistle, poppy, nut, canola, soy, sunflower, isoaliphates, and lead-free drying agents (white color shade: additionally titanium white and lead-free drying agents).

Note: Ensure good ventilation at all times (open doors).

Although our products are naturel and ecological please;

- Keep out of reach of children. May cause allergic reactions.
- Completely empty containers before recycling.
- Dried waste material can be disposed of as household waste or construction waste.
- Liquid disposed of at paint collection facility.
- In case of contact with the skin, rinse immediately with clear water.
- It must not be allowed to escape into the sewage system or in flowing water.

Disclaimer

Our technical advice in written form is given in good faith and on the basis of experiments, but it is only non-binding advice and does not release you from the obligation to test the products supplied by us as to their suitability for the particular purpose. Application, use and processing of the products outside our direct control are entirely your responsibility. Naturally we guarantee consistent quality of our products corresponding to the original sample. With release of new product information the previous information loses validity.

Whittle Waxes Victoria 6/9 Pilgrim Court Ringwood VIC 3134 Ph: 03 9873 848

1300 ECOWAX (1300 326 929) info@whittlewaxes.com.au www.whittlewaxes.com.au