



Product Description: Whittle Waxes Wood Filler

A clear wood filler solution which is designed to be mixed with sawdust, to fill cracks in timber and parquet floors.

Properties: Provides good binding and adhesive strength, quick drying and extreme hardness.

Simple: Is easy to sand and simple to apply, provides low shrinkage in the joints.

When dry: Wood Filler is coatable with all Whittle Waxes products.

Areas of use: Serves as a bonding agent for saw dust, which must be wax and paint free. For the initial filling of parquet and wooden floors and to seal joints (ideally 100 or 120 grit sanding dust).

Recommended Tools: Trowel, 100/120 grit sand paper and sanding dust, stirring stick.

Clean tools: with WHITTLE WAXES SPECIAL-THINNER and newspaper or similar paper.

Coats needed: Single coat system

Sheen Levels: N/A

Container sizes: 1L, 5L and larger.

Coverage Rate: 40 to 100g/m² dependent on the size of the joints. Apply as little as possible.

Drying time: Stated drying times are based on normal conditions (+20°C and 55% rel. humidity). The room/surface should not be below 15°C when applying.

Storage: Storage period of 1 year in the unopened original container. Opened containers should be well closed and used promptly. Cool and frost-free. Recommended storage temperature: Above 8°C.

Note: Highly flammable. Usage generates explosive, highly flammable vapors

Sanding & Preparation:

1. Save the saw dust from your last clean sanding (2nd or 3rd sanding, 100/120 grit)
2. Usage: Use undiluted. Mix with saw dust into a homogenous, easily workable paste and then work into the joints with a trowel.
3. The trowel application should be carried out such that only the joints are filled as far as possible.
4. After a minimum of 15 minutes, light sanding is required.
5. Respect drying time and coat with your choice of Whittle Waxes or Treatex products (including Colours)

Ingredients: Mixed polymerizate, microcellulose.

International GHS Safety Notes: P101 If medical advice is needed, keep packaging or label handy. P102 Keep out of the reach of children. P103 Read label before use. P271 Use only outdoors or in well-ventilated areas. P305 + P351 + P338 IF IN CONTACT WITH THE EYES: For a few minutes, rinse carefully with water. Remove contact lenses if possible. Continue rinsing. P370 + P378 In the event of fire: Use dry chemical or sand for extinguishing. P403 + P233 Keep container tightly closed in a well-ventilated place. P403 + P235 Store in a well-ventilated place. P405 Store locked up. P501 Dispose of contents/container at an industrial waste incineration plant. Only completely emptied containers may be recycled. Dispose of liquid residues at a collection point for old paint. ASN No.: 080111.

Disclaimer: Our technical advice in written form is given in good faith and on the basis of experiments, but it is only non-binding advice and does not release you from the obligation to test the products supplied by us as to their suitability for the particular purpose. Application, use and processing of the products outside our direct control are entirely your responsibility. Naturally we guarantee consistent quality of our products corresponding to the original sample. With release of new product information the previous information loses validity.