

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) No 453/2010

Article No.: 30312
Print date: 14.09.2016
Version: 7.4

Whittle Waxes Hard Wax Oil
Revision date: 13.09.2016
Issue date: 13.09.2016

EN
Page 1 / 7

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. **product identifiers**

Article No. (manufacturer/supplier) 30312
Identification of the substance or mixture Whittle Waxes Hard Wax Oil
Primer Mixture

1.2. **Relevant identified uses of the substance or mixture and uses advised against**

Relevant identified uses

Wood treatment
Surface protection

1.3. **Details of the supplier of the safety data sheet**

supplier (manufacturer/importer/downstream user/distributor)

WHITTLEWAXES Pty Ltd.
Factory 13, 25 Quanda Rd, Coolum Beach Telephone: + 61 07 5471 7963
QLD 4573,
Australia info@whittlewaxes.com.au
www.whittlewaxes.com.au

Dept. responsible for information:

Sale + 61 07 5471 7963
E-mail (competent person) info@whittlewaxes.com.au

1.4. **Emergency telephone number**

+ 61 1300 326 929

SECTION 2: Hazards identification

2.1. **Classification of the substance or mixture**

Classification according to Regulation (EC) No 1272/2008 [CLP]

This mixture is classified as not hazardous according to regulation (EC) No 1272/2008 [CLP].

2.2. **Label elements**

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms

Hazard statements

not applicable

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of the reach of children.
P103 Read label before use.

contains:

not applicable

Supplemental Hazard information (EU)

EUH208 Contains Cobalt bis (2-ethylhexanoate). May produce an allergic reaction.
EUH210 Safety data sheet available on request.

2.3. **Other hazards**

SECTION 3: Composition / information on ingredients

3.2. **Mixtures**

Product description / chemical characterization

Description Solvent-borne paints

Hazardous ingredients

Classification according to Regulation (EC) No 1272/2008 [CLP]

EC No.	REACH No.	Wt %
CAS No.	Chemical name	Remark
INDEX No.	classification:	

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) No 453/2010

Article No.: 30312 Whittle Waxes Hard Wax Oil
Print date: 14.09.2016 Revision date: 13.09.2016 EN
Version: 7.4 Issue date: 13.09.2016 Page 2 / 7

918-481-9	01-2119457273-39	
64742-48-9	hydrocarbons, C10-C13, n-alkane, iso-alkane, cyclic compound, < 2 %	50 - 70
649-327-00-6	aromatics Asp. Tox. 1 H304	
205-250-6	01-2119524678-29-XXXX	
136-52-7	Cobalt bis (2-ethylhexanoate) Eye Irrit. 2 H319 / Skin Sens. 1 H317 / Repr. 2 H361 / Aquatic Acute 1 H400 / Aquatic Chronic 3 H412	0,1 - 0,15
245-018-1		
22464-99-9	2-ethylhexanoic acid, zirconium Repr. 2 H361	0,1 - 0,15

Additional information

Full text of H-phrases: see section 16.

This mixture does not contain any substances which either present a health or environmental hazard according to directive 67/548/EEC or have an occupational exposure limit assigned.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

In case of inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

Following skin contact

Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

After ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

In all cases of doubt, or when symptoms persist, seek medical advice.

4.3. Indication of any immediate medical attention and special treatment needed

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

alcohol resistant foam, carbon dioxide, Powder, spray mist, (water)

Extinguishing media which must not be used for safety reasons:

strong water jet

5.2. Special hazards arising from the substance or mixture

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

5.3. Advice for firefighters

Provide a conveniently located respiratory protective device. Cool closed containers that are near the source of the fire. Do not allow water used to extinguish fire to enter drains, ground or waterways. Treat runoff as hazardous.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Ventilate affected area. Do not breathe vapours. See protective measures under point 7 and 8.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) No 453/2010

Article No.: 30312 Whittle Waxes Hard Wax Oil
Print date: 14.09.2016 Revision date: 13.09.2016
Version: 7.4 Issue date: 13.09.2016

EN
Page 3 / 7

6.3. Methods and material for containment and cleaning up

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13). Clean using cleansing agents. Do not use solvents.

6.4. Reference to other sections

Observe protective provisions (see chapter 7 and 8).

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advices on safe handling

Avoid contact with skin, eyes and clothes. Avoid respiration of swarf. When using do not eat, drink or smoke. Personal protection equipment: refer to section 8. Do not empty containers with pressure - no pressure vessel! Always keep in containers that correspond to the material of the original container. Follow the legal protection and safety regulations.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks. Soils have to conform to the "Guidelines for avoidance of ignition hazards due to electrostatic charges (BGR 132)".

Hints on joint storage

Keep away from strongly acidic and alkaline materials as well as oxidizers.

Further information on storage conditions

Store in a well-ventilated and dry room at temperatures between 15 °C and 30 °C. Keep container tightly closed. Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

7.3. Specific end use(s)

Observe technical data sheet. Observe instructions for use.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limit values:

Cobalt bis (2-ethylhexanoate)
EC No. 205-250-6 / CAS No. 136-52-7
TWA: 0,1 mg/m³

2-ethylhexanoic acid, zirconium
EC No. 245-018-1 / CAS No. 22464-99-9
TWA: 5 mg/m³
STEL: 10 mg/m³

Additional information

TWA : long-term occupational exposure limit value
STEL : short-term occupational exposure limit value
Ceiling : peak limitation

DNEL:

Cobalt bis (2-ethylhexanoate)
EC No. 205-250-6 / CAS No. 136-52-7
DNEL long-term inhalative (systemic), Workers: 0,2351 mg/m³
DNEL long-term oral (repeated), Consumer: 0,0558 mg/kg
DNEL long-term inhalative (systemic), Consumer: 0,037 mg/m³
No data available

2-ethylhexanoic acid, zirconium
EC No. 245-018-1 / CAS No. 22464-99-9
DNEL long-term dermal (systemic), Workers: 15,75 mg/kg

PNEC:

Cobalt bis (2-ethylhexanoate)
EC No. 205-250-6 / CAS No. 136-52-7

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) No 453/2010

Article No.: 30312 Whittle Waxes Hard Wax Oil
Print date: 14.09.2016 Revision date: 13.09.2016
Version: 7.4 Issue date: 13.09.2016

EN
Page 4 / 7

PNEC aquatic, freshwater: 0,0005 mg/L
PNEC sediment, marine water: 9,5 mg/kg
PNEC, Soil: 7,9 mg/kg
PNEC sewage treatment plant (STP): 0,37 mg/L

2-ethylhexanoic acid, zirconium
EC No. 245-018-1 CAS No. 22464-99-9
PNEC aquatic, freshwater: 0,36 mg/L
PNEC aquatic, marine water:
PNEC sediment, marine water:

8.2. Exposure controls

Provide good ventilation. This can be achieved with local or room suction.

Occupational exposure controls

Respiratory protection

Not applicable.

Hand protection

For prolonged or repeated handling the following glove material must be used: e.g. Nitrile (according to DIN EN 374)

Thickness of the glove material 0,4 mm Breakthrough time (maximum wearing time) 30 min

Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles DIN EN 374

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

Eye protection

Wear closely fitting protective glasses in case of splashes.

Protective clothing

Wear suitable protective clothing and gloves.

Protective measures

After contact clean skin thoroughly with water and soap or use appropriate cleanser.

Environmental exposure controls

Do not allow to enter into surface water or drains. See chapter 7. No additional measures necessary.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance:

Physical state liquid
Colour refer to label
Odour characteristic

Safety relevant basis data	Unit	Method	Remark
Flash point:	Not applicable °C	DIN 13736	
Ignition temperature in °C:	200 °C	calculated	
Lower explosion limit:	0,6 Vol-%	calculated	
Upper explosion limit:	7 Vol-%	calculated	
Vapour pressure at 20 °C:	not applicable	calculated	
Density at 20 °C:	0,888 g/cm ³	DIN 53217	
Water solubility (g/L):	insoluble		
pH at 20 °C:	-		
Viscosity at 20 °C:	39 s 4 mm	DIN 53211	
Solid content (%):	44 Wt %		
solvent content:			
Organic solvents:	54 Wt %		
Water:	0 Wt %		

9.2. Other information

SECTION 10: Stability and reactivity

10.1. Reactivity

10.2. Chemical stability

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to chapter 7.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) No 453/2010

Article No.: 30312 Whittle Waxes Hard Wax Oil
Print date: 14.09.2016 Revision date: 13.09.2016
Version: 7.4 Issue date: 13.09.2016

EN
Page 5 / 7

10.3. Possibility of hazardous reactions

Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.

10.4. Conditions to avoid

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to chapter 7. Hazardous decomposition byproducts may form with exposure to high temperatures.

10.5. Incompatible materials

10.6. Hazardous decomposition products

Hazardous decomposition byproducts may form with exposure to high temperatures, e.g.: carbon dioxide, carbon monoxide, smoke, nitrogen oxides.

SECTION 11: Toxicological information

No data on preparation itself available.

11.1. Information on toxicological effects

Acute toxicity

Cobalt bis (2-ethylhexanoate)
oral, LD50, Rat:

hydrocarbons, C10-C13, n-alkane, iso-alkane, cyclic compound, < 2 % aromatics
inhalative (vapours), LC50, Rat: > 20 mg/L (4 h)

Irritant and corrosive effects

Cobalt bis (2-ethylhexanoate)
Skin (4 h)
eyes

Sensitisation

Cobalt bis (2-ethylhexanoate)
Skin:

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Cobalt bis (2-ethylhexanoate)
Reproductive toxicity

2-ethylhexanoic acid, zirconium
Reproductive toxicity

Specific target organ toxicity

Cobalt bis (2-ethylhexanoate)
Specific target organ toxicity (single exposure), Irritation:

Aspiration hazard

Toxicological data are not available.

Practical experience/human evidence

Other observations:

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

Overall Assessment on CMR properties

The ingredients in this preparation do not meet the criteria for classification as CMR category 1 or 2 according to 67/548/EEC.

Remark

There is no information available on the preparation itself .

SECTION 12: Ecological information

overall evaluation

There is no information available on the preparation itself .
Do not allow to enter into surface water or drains.

12.1. Toxicity

Cobalt bis (2-ethylhexanoate)
Fish toxicity, LC50: 0,1 - 1 mg/L (96 h)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) No 453/2010

Article No.: 30312 Whittle Waxes Hard Wax Oil
Print date: 14.09.2016 Revision date: 13.09.2016
Version: 7.4 Issue date: 13.09.2016

EN
Page 6 / 7

Daphnia toxicity, EC50: 0,1 - 1 mg/L (48 h)
Algae toxicity, ErC50, Algae: 0,1 - 1 mg/L
hydrocarbons, C10-C13, n-alkane, iso-alkane, cyclic compound, < 2 % aromatics
Fish toxicity, LC50: > 1000 mg/L (96 h)
Daphnia toxicity, EC50: > 1000 mg/L (48 h)
Algae toxicity, ErC50: > 1000 mg/L

Long-term Ecotoxicity

Cobalt bis (2-ethylhexanoate)
Fish toxicity, LC50: (96 h)
Daphnia toxicity, EC50: (48 h)
Algae toxicity, ErC50:

12.2. Persistence and degradability

Toxicological data are not available.

12.3. Bioaccumulative potential

Toxicological data are not available.

Bioconcentration factor (BCF)

Toxicological data are not available.

12.4. Mobility in soil

Toxicological data are not available.

12.5. Results of PBT assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Other adverse effects

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Appropriate disposal / Product Recommendation

Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

List of proposed waste codes/waste designations in accordance with EWC

080112 waste paint and varnish other than those mentioned in 080111

packaging

Recommendation

Non-contaminated packages may be recycled. Vessels not properly emptied are special waste.

SECTION 14: Transport information

This mixture is not classified as dangerous according to international transport regulations (ADR/RID, IMDG, ICAO/IATA).

No dangerous good in sense of this transport regulation.

14.1. UN number

not applicable

14.2. UN proper shipping name

14.3. Transport hazard class(es)

not applicable

14.4. Packing group

not applicable

14.5. Environmental hazards

Land transport (ADR/RID)

not applicable

Marine pollutant

not applicable

14.6. Special precautions for user

Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage.

Advices on safe handling: see parts 6 - 8

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) No 453/2010

Article No.: 30312
Print date: 14.09.2016
Version: 7.4

Whittle Waxes Hard Wax Oil
Revision date: 13.09.2016
Issue date: 13.09.2016

EN
Page 7 / 7

Additional information

Land transport (ADR/RID)

tunnel restriction code -

Sea transport (IMDG)

EmS-No. not applicable

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Information according to 1999/13/EC about limitation of emissions of volatile organic compounds (VOC-guideline).

VOC-value (in g/L) ISO 11890-2: 494,533

VOC-value (in g/L) ASTM D 2369: 494,533

according to EU-regulation 2004/42/EC (appendix II)

EU limit value for this product (cat. (Cat. A/i)): 600 g/l (2007)/500 g/l (2010).

This product contains max 494,533 g/l VOC.

National regulations

Restrictions of occupation

Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).

Other regulations, restrictions and prohibition regulations

15.2. Chemical Safety Assessment

For the following substances of this preparation a chemical safety assessment has been carried out:

EC No. CAS No.	Chemical name	REACH No.
918-481-9 64742-48-9	hydrocarbons, C10-C13, n-alkane, iso-alkane, cyclic compound, < 2 % aromatics	01-2119457273-39
205-250-6 136-52-7	Cobalt bis (2-ethylhexanoate)	01-2119524678-29-XXXX

SECTION 16: Other information

Relevant R-and H-phrases (Number and full text):

Asp. Tox. 1 / H304	Aspiration hazard	May be fatal if swallowed and enters airways.
Eye Irrit. 2 / H319	Serious eye damage/eye irritation	Causes serious eye irritation.
Skin Sens. 1 / H317	Respiratory or skin sensitisation	May cause an allergic skin reaction.
Repr. 2 / H361	Reproductive toxicity	Suspected of damaging fertility or the unborn child (state specific effect if known) (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard).
Aquatic Acute 1 / H400	Hazardous to the aquatic environment	Very toxic to aquatic organisms.
Aquatic Chronic 3 / H412	Hazardous to the aquatic environment	Harmful to aquatic life with long lasting effects.

Additional information

The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and EU regulations. Without written approval, the product must not be used for purposes different from those mentioned in chapter 1. It is always the user's duty to take any necessary measures for meeting the requirements laid down by local rules and regulations. The details in this safety data sheet describe the safety requirements of our product and are not to be regarded as guaranteed attributes of the product.