



whittle
W A X E S

For Beautiful Timber, Naturally

Product Information

Whittle Waxes WOOD MAGIC

Care product for all types of timber, both interior and exterior, such as teak, yellow-ballau, oak.

Whittle Waxes WOOD MAGIC for the protection and care of the timber from environmental and climatic influences, UV rays, water and dirt.

The solvent-free care emulsion refreshes faded and greyed furniture, restoring the colour as well as re-establishing its water repellent and UV resistant properties.

Application / processing:

- The untreated surface must be clean, dry, dust and grease free.
- Before and during use, shake well.
- Timber must have a moisture content no higher than 18%.
- Appearance may differ on different surfaces. Trial coats are essential.

Apply: *Whittle Waxes WOOD MAGIC* with a brush or roller.

Greyed surfaces need cleaning with Teak Cleaner prior to treatment. Use fine sandpaper or sanding sponge to remove more stubborn stains and then treated with *Whittle Waxes WOOD MAGIC*. Apply 2 coats.

Usage: About. 100 ml / m, i.e. 1 liter of *Whittle Waxes WOOD MAGIC* is sufficient for approx. 10 sqm per coat, depending on the timber and surface (planed or rough sawn).

Drying time: at least 24 hours (weather permitting), Processing temperature (including drying) from +8 ° C.

Care: A re-treatment should be made as needed 1-2 times a year.

Cleaning: Clean tools with soap and water.

Storage: Cool, but frost-free. In the unopened container 3 years.

Pack Size: 1 liter

Ingredients:

Water, purified natural oils, lead-free driers, waxes. Preservatives
This product contains a maximum of 1 g / 1 VOC.



whittle
W A X E S



Although our products are natural and ecological please;

- Keep out of reach of children. May cause allergic reactions.
 - Completely empty containers before recycling.
 - Dried waste material can be disposed of as household waste or construction waste.
 - Liquid disposed of at paint collection facility.
 - In case of contact with the skin, rinse immediately with clear water.
 - It must not be allowed to escape into the sewage system or in flowing water.
- *Do not leave waste sanding powder in vacuum unit

Disclaimer

Our technical advice in written form is given in good faith and on the basis of experiments, but it is only non-binding advice and does not release you from the obligation to test the products supplied by us as to their suitability for the particular purpose. Application, use and processing of the products outside our direct control are entirely your responsibility.

Naturally we guarantee consistent quality of our products corresponding to the original sample. With release of new product information the previous information loses validity.